

KENWOOD

Listen to the Future



TK-5210/5310

VHF/UHF FM & Project 25 Digital Portable Radios



FleetSync[®]
by KENWOOD

GENERAL FEATURES

- 5 Watt (136-174 MHz)
- 4 Watt (450-520, 380-470 MHz)
- 50 Zones / 512 Channels (K-K6)
- 16 Zones / 64 Channels (K7)
- Personality Lists
- Backlit Dot Matrix LCD¹
- 16 Character Alphanumeric Aliases¹
- 3-Digit Sub-Display¹
- Function / Status LCD Icons¹
- RSSI Indicator
- Transmit / Busy / Call Alert / Warn LED
- On/Off Volume Knob
- 16-Position Selector Knob
- 2-Position PF Lever Switch
- 3-Position PF Concentric Switch
- 4 Front Menu-Driven PF Keys¹
- 3 Side PF Keys
- Orange Emergency / AUX Key
- 12-Key DTMF / PF Keypad²
- Enhanced Kenwood Audio
- Voice Annunciation
- VOX Ready
- Emergency Features
- Tactical Group¹
- Battery Level Indicator¹

- Transceiver Password¹
- Date & 12/24 Hour Time Clock¹
- Windows[®] Programming & Tuning³
- Windows[®] Firmware Uploading³
- Self-Programming & Tuning¹
- Cloning¹
- Easy Option Port
- Weather-Sealed Accessory Connector
- MIL-STD-810 C/D/E/F
- IP54/55 Water & Dust Protection
- Immersion (IP66/67) Option
- Intrinsically Safe Option

SCAN TYPES (FM & P25)

- Single Zone/Multi-Zone Scan
- Scan Lists
- Conventional Scan
- Limited Talk Group Scan⁴
- Priority Monitor Scan⁴
- Dual Priority Scan

FM

- QT / DQT
- Operator Selectable Tone
- Two-Tone Decode / Encode
- DTMF Encode / Decode / Stun
- Special Alert Tone Patterns⁵
- Encryption / ANI Board Control
- Companded Audio

FleetSync[®] (FM)

- FleetSync[®] or FleetSync[®] II
- PTT ID Digital ANI
- Caller ID Display
- Status Messaging
- Emergency & Stun Statuses
- Selective & Group Call
- Text Messaging

P25 DIGITAL

- P25 Digital Conventional
- P25 Digital Trunking Option
- IMBE[™] VOCODER
- Talk Group ID Lists
- Individual ID Lists
- Caller ID Display
- Remote Monitor/Remote Check
- Radio Inhibit
- Encryption Key Delete
- Encryption Key Zeroize (SCM required)
- Encryption Key Retention (SCM required)
- DES Encryption Options
- AES / DES Encryption Options⁷
- KPG-93 KVL Key Loader Interface Cable⁶



Three models available:
Basic Unit: No LCD, No front Keys
16-Character LCD, 4 Menu-driven PF Keys
16-Character LCD, 4 Menu-driven PF Keys, 12-Key DTMF/PF Keypad
(Not actual size)

